

6-SERIES LIVE GUARD SYSTEM

SPECIFICATIONS



FORM FACTOR

Dimensions: 8'L x 5'W x 10'H
Mast: Aluminum Alloy, Telescopic
to 20', Manual Winch,
Spring Cable
Trailer: 2" Ball Hitch, Single Axle,
Manual Outriggers



*EQUIPMENT NOT SHOWN IN PICTURE

EQUIPMENT & FEATURES

- ▶ (4) Axis P1455-LE Network Bullet Camera
- ▶ (1) Pyle 30 watt Loudspeaker
- ▶ (2) High Intensity Blue/Red Strobe Lights

Analytics & Software:

Live Shield Advanced Video Monitoring Services &
Mobile Application

Details: www.onsightlive.com/live-shield

 **1833 346 5483**

Contact Us

4904 S Power Rd Ste 103-208 Mesa, AZ 85212
www.onsightlive.com / email: contact@onsightlive.com

LIKE US : [FACEBOOK.COM/ONSIGHTLIVESURVEILLANCE](https://www.facebook.com/ONSIGHTLIVESURVEILLANCE)

WWW.ONSIGHTLIVE.COM/LIVE-GUARD



POWER & NETWORK



Solar Panel: 2 x 380W Solar Panel
Battery: 4 x 150Ah 12VDC Battery
Charge Controller: 30A MPPT
Plug-in Charger: 2kW/2kVA AC220V/110V



Network: Industrial Grade 4G LTE Router
& 12VDC POE Switch